

Serial No. 09/607007

- 3 -

Art Unit:2143

REMARKS

Reconsideration and further examination is respectfully requested.

Objections to the Disclosure

The disclosure was objected to for failure to appropriately indicate trademark ownership status. Applicants have amended the specification to correct this oversight, and it is respectfully requested that the objection be withdrawn.

Rejections under 35 U.S.C. §102

Claims 1-152 were rejected under 35 U.S.C. §102(b) as being anticipated by Mitra, U.S. Patent 5,748,736.

It is noted that in order to support a rejection under 35 U.S.C. §102, *every* limitation in the claim must be found or suggested in the prior art. As will be described below, the key distribution scheme described in Mitra is different than that recited in the claimed invention, and for at least this reason the rejection under 35 U.S.C. §102 is improper.

Mitra

Mitra describes, at column 7, lines 45-65:

“...Joining a secure multicast group requires the joining member first to set up a separate secure channel with the GSC of the group (using a unicast communication line). The purpose of the secure channel is to facilitate and isolate confidential communication between the GSC and this member during the time that the member is part of the group... Upon receiving a join request (and approving it), the GSC inserts the member's identification and information concerning the secure channel in a private database it maintains. In this way the GSC has full knowledge of the group membership and can communicate with each member separately and securely when

Serial No. 09/607007

- 4 -

Art Unit:2143

required. The member must also store information concerning the secure channel for future communication with the GSC... All communications from the GSC must include a message digest and be digitally signed so that receivers may verify that the message has not been corrupted and the sender was actually the GSC... Only the GSC maintains information concerning group membership; members do not know about each other (except that receivers may need to know the list of authorized senders)...”

Mittra also states, at column 8, lines 14-22:

“...Once the GSC and the new member have authenticated each other and have agreed on a secret the GSC needs to provide the new member with information that will allow it to encrypt and/or decrypt the multicast transmission. At this point the GSC also needs to change the group key (Kgrp) which provides access to the multicast transmissions. This is done to prevent the joining member from decrypting previous transmissions to which it should not have access...”

Accordingly, Mittra describes a method by which authorization of a member is performed by the provider of the key (the GSC) when a device wishes to join a group. Once that key exchange has occurred, then a group key is distributed to all members of the group. Note that Mittra explicitly states “... members do not know about each other...”

In contrast, claim 1 as amended recites “...A communication system comprising .. a plurality of multicast devices forming a shared multicast distribution tree a host device; a key server; and a designated device, separate from the key server, through which the host device accesses the shared tree, wherein the host device obtains access information from the key server for the host device to access the shared tree, the access information including authentication information unique to the host device; the designated device obtains the access information associated with the host device from the key server for enabling the host device to access the shared tree; the host device sends an access control message to the designated device to join the shared tree; and the designated device uses the access information to authenticate the host device before adding the host device to the shared tree...”

Serial No. 09/607007

- 5 -

Art Unit:2143

No such structure, wherein access information unique to the host device is forwarded by the key server to both a host and another device (the designated device) is shown or suggested in Mitra. Rather, Mitra establishes a secure channel between the GSC and the member for the purposes of allowing the member to join the group. Then, a group key, *not* the secure channel information, is forwarded to other members of the group. As explicitly stated in Mitra 'members do not know about each other...'

Accordingly, for at least the reason that every limitation of claim 1 is neither described nor suggested in Mitra, the rejection under 35 U.S.C. §102 should be withdrawn. Independent claims 16, 28, 40, 61, 68, 75, 87, 99 and 122 have been amended to include limitations similar to those of claim 1 which assist to distinguish the claims over Mitra, and thus the rejection under 35 U.S.C. §102 for these claims should be withdrawn as well. Dependent claims 2-15, 17-27, 29-39, 41-60, 69-74, 76-86, 88-98, 100-121 and 122-144 serve to add further patentable limitations to their parent independent claims, but are allowable for at least the reason put forth above with regard to their parent independent claim.

Independent claim 145 has been amended to include a limitation of claim 147, and claim 147 has been cancelled. Independent claim 45 as amended now recites "...A communication message embodied in a data signal, the communication message comprising a group key for a multicast group and access information for a host device, *wherein the access information comprises an expiration date for the authentication key...*"

Serial No. 09/607007

- 6 -

Art Unit:2143


The Examiner states, at page 13 of the office action '...for an authentication to function properly, it inherently must possess an expiration method of some sort...' This appears to be an assumption of the Examiner, although official notice has not been taken, and does not appear to be based on any teaching of any reference provided, including Mitra. Accordingly, because each limitation of the claim is not shown or suggested in the Mitra reference, the rejection of claim 145 and associated dependent claims under 35 U.S.C. §102 is improper, and should be withdrawn.

Applicants have made a diligent effort to place the claims in condition for allowance. However, should there remain unresolved issues that require adverse action, it is respectfully requested that the Examiner telephone Lindsay G. McGuinness, Applicants' Attorney at 978-264-6664 so that such issues may be resolved as expeditiously as possible.

For these reasons, and in view of the above amendments, this application is now considered to be in condition for allowance and such action is earnestly solicited.

Respectfully Submitted,

9/10/2004
Date


Lindsay G. McGuinness, Reg. No. 38,549
Attorney/Agent for Applicant(s)
Steubing McGuinness & Manaras LLP
125 Nagog Park Drive
Acton, MA 01720
(978) 264-6664

Docket No. 120-147
Dd: 6/30/2004

Serial No. 09/607007

- 7 -

Art Unit:2143

CLAIMS

1. (currently amended) A communication system comprising:

a plurality of multicast devices forming a shared multicast distribution tree;

a host device; ~~and~~

a key server; and

a designated device, separate from the key server, through which the host device accesses the shared tree, wherein:

the host device obtains access information from the key server for the host device to access the shared tree, the access information including authentication information unique to the host device;

the designated device obtains the access information associated with the host device from the key server for enabling the host device to access the shared tree;

the host device sends an access control message to the designated device to join the shared tree; and

the designated device uses the access information to authenticate the host device before adding the host device to the shared tree.

2. (currently amended) The communication system of claim 1, ~~further comprising a~~ wherein the key server includes logic for authenticating the host device and generating the access information for the host device to access the shared tree.

3. (original) The communication system of claim 2, wherein the key server provides the access information to the host device over a secure communication channel.

4. (original) The communication system of claim 2, wherein the key server provides the access information to the designated device using a unicast distribution mechanism.

5. (original) The communication system of claim 2, wherein the key server provides the access information to the designated device using a multicast distribution mechanism.

Serial No. 09/607007

- 8 -

Art Unit:2143

6. (original) The communication system of claim 2, wherein the key server provides the access information to the designated device using a broadcast distribution mechanism.

7. (original) The communication system of claim 2, wherein the designated device requests the access information from the key server upon receiving the access control message.

8. (original) The communication system of claim 2, wherein the key server provides the access information to the plurality of multicast devices forming the shared tree.

9. (original) The communication system of claim 1, wherein the access information comprises:
a token identifier; and an authentication key.

10. (original) The communication system of claim 9, wherein the access control message comprises the token identifier.

11. (original) The communication system of claim 10, wherein the access control message is an Internet Group Management Protocol (IGMP) join request including the token identifier.

12. (original) The communication system of claim 1, wherein the designated device joins the shared tree on behalf of the host device upon authenticating the host device.

13. (original) The communication system of claim 12, wherein the shared tree is a Protocol Independent Multicast (PIM) shared tree, and wherein the designated device sends a PIM join request upstream toward a rendezvous point device in order to join the shared tree on behalf of the host device upon authenticating the host device.

14. (original) The communication system of claim 1, wherein the designated device forwards the access control message to a neighboring device upon failing to authenticate the host device using the access information.

Serial No. 09/607007

- 9 -

Art Unit:2143

15. (original) The communication system of claim 14, wherein the neighboring device obtains the access information and authenticates the host device using the access information.

16. (currently amended) A method performed at a key server comprising:

 authenticating a host device;

 generating access information by the key server for the host device to join a multicast group, the access information including authentication information unique to the host device;

 sending the access information to the host device; and sending the access information to a separate designated device for the through which host device gains access to a shared multicast distribution tree.

17. (original) The method of claim 16, wherein the access information comprises:

a token identifier; and an authentication key.

18. (original) The method of claim 17, wherein the access information further comprises an expiration date for the authentication key.

19. (original) The method of claim 17, wherein the access information further comprises a public key.

20. (original) The method of claim 16, wherein sending the access information to the host device comprises:

 sending a communication message including the access information to the host device over a secure communication channel.

21. (original) The- method of claim 20, wherein the communication message is a group key management communication message.

22. (original) The method of claim 16, wherein sending the access information to the designated device for the host device comprises:

Serial No. 09/607007

- 10 -

Art Unit:2143

sending a communication message including the access information to the designated device over a secure communication channel.

23. (original) The method of claim 22, wherein the communication message is a unicast communication message addressed to the designated device.

24. (original) The method of claim 22, wherein the communication message is a multicast communication message addressed to a multicast group of which the designated device is a member.

25. (original) The method of claim 22, wherein the communication message is a broadcast communication message.

26. (original) The method of claim 16, wherein generating the access information comprises:
generating an access token including the access information.

27. (original) The method of claim 26, wherein the access token comprises:
a group identifier for identifying a multicast group;
a host identifier for identifying the host device;
a token identifier for identifying the access token;
an authentication key for the host device;
an expiration date for the authentication key;
a server identifier for identifying a key server; and a public key for the key server.

28. (currently amended) A method performed at a host device comprising:
obtaining access information from a key server for joining a multicast group from an access information server, the access information including authentication information unique to the host device;
generating an access control message for joining the multicast group using the access information; and

Serial No. 09/607007

- 11 -

Art Unit:2143

sending the access control message to a designated device separate from the key server for enabling the host device to join ~~joining~~ the multicast group.

29. (original) The method of claim 28, wherein the access information comprises:
a token identifier; and an authentication key.

30. (original) The method of claim 29, wherein generating the access control message using the access information comprises:

including the token identifier in the access control message.

31. (original) The method of claim 28, further comprising:

generating authentication information using the access information; and sending the authentication information to the designated device.

32. (original) The method of claim 31, wherein generating the authentication information using the access information comprises generating a digital signature using the access information and a predetermined digital signature scheme.

33. (original) The method of claim 32, wherein the predetermined digital signature scheme comprises a keyed hash function.

34. (original) The method of claim 33, wherein the keyed hash function comprises GPsec AH with HMAC-MD5.

35. (original) The method of claim 33, wherein the keyed hash function comprises IPsec AH with HMAC-SHA1.

36. (original) The method of claim 29, wherein the access information further comprises a token identifier.

Serial No. 09/607007

- 12 -

Art Unit:2143

37. (original) The method of claim 36, wherein generating the access control message using the access information comprises:

including the token identifier in the access control message.

38. (original) The method of claim 37, wherein the access control message is an Internet Group Management Protocol (IGMP) join request message including the token identifier.

39. (original) The method of claim 28, further comprising:
establishing a security agreement with the designated device using the access information.

40. (currently amended) A method performed at a designated device that controls access to a shared multicast tree comprising:

receiving an access control message from a host device;

determining whether the host device is authorized to access a shared multicast distribution tree based upon access information for the host device, the access information including authentication information unique to the host device and being received by the designated device from a separate key server; and

joining the shared tree on behalf of the host device if the host device is determined to be authorized to access the shared tree.

41. (original) The method of claim 40, further comprising:
obtaining the access information for the host device.

42. (original) The method of claim 41, wherein obtaining the access information for the host device comprises:

receiving the access information from an access information server prior to receiving the access control message from the host device.

43. (original) The method of claim 41, wherein obtaining the access information for the host device comprises:

Serial No. 09/607007

- 13 -

Art Unit:2143

requesting the access information from an access information server after receiving the access control message from the host device.

44. (original) The method of claim 40, wherein determining whether the host device is authorized to access the shared tree comprises:

- maintaining an access information database;
- searching the access information database for the access information for the host device;
- failing to find the access information for the host device in the access information database; and
- determining that the host device is not authorized to access the shared tree.

45. (original) The method of claim 40, wherein determining whether the host device is authorized to access the shared tree comprises:

- maintaining an access information database;
- searching the access information database for the access information for the host device;
- failing to find the access information for the host device in the access information database; and
- forwarding the access control message to a neighboring device.

46. (original) The method of claim 40, wherein the access information comprises:
a token identifier; and an authentication key.

47. (original) The method of claim 46, wherein the access control message includes the token identifier.

48. (original) The method of claim 46, wherein the access information further comprises an expiration date for the authentication key.

49. (original) The method of claim 48, wherein determining whether the host device is authorized to access the shared tree comprises:

Serial No. 09/607007

- 14 -

Art Unit:2143

determining that the authentication key has expired based upon the expiration date for the authentication key; and

determining that the host device is not authorized to access the shared tree.

50. (original) The method of claim 48, wherein determining whether the host device is authorized to access the shared tree comprises:

determining that the authentication key has expired based upon the expiration date for the authentication key; and

forwarding the access control message to a neighboring device.

51. (original) The method of claim 40, wherein determining whether the host device is authorized to access the shared tree comprises:

authenticating the host device using the access information and a predetermined authentication scheme; and

determining whether the host device is authorized to access the shared tree based upon authenticating the host device using the access information and the predetermined authentication scheme.

52. (original) The method of claim 51, wherein authenticating the host device using the access information and the predetermined authentication scheme comprises:

receiving authentication information from the host device; and authenticating the host device based upon the access information and the authentication information received from the host device.

53. (original) The method of claim 52, wherein the authentication information comprises a digital signature, and wherein authenticating the host device based upon the access information and the authentication information received from the host device comprises:

verifying the digital signature using the access information and a predetermined digital signature scheme.

Serial No. 09/607007

- 15 -

Art Unit:2143

54. (original) The method of claim 53, wherein the predetermined digital signature scheme comprises a keyed hash function.

55. (original) The method of claim 54, wherein the keyed hash function comprises IPsec AH with HMAC-MD5.

56. (original) The method of claim 54, wherein the keyed hash function comprises IPsec AH with HMAC-SHA1.

57. (original) The method of claim 51, wherein determining whether the host device is authorized to access the shared tree based upon authenticating the host device using the access information and the predetermined authentication scheme comprises:
determining that authentication failed;

determining that the host device is not authorized to access the shared tree.

58.(original) The method of claim 57, further comprising:

forwarding the access control message to a neighboring device.

59. (original) The method of claim 51, wherein determining whether the host device is authorized to access the shared tree based upon authenticating the host device using the access information and the predetermined authentication scheme comprises:

determining that authentication succeeded; and

determining that the host device is authorized to access the shared tree.

60. (original) The method of claim 40, further comprising:

establishing a security association with the host device using the access information upon determining that the host device is authorized to access the shared tree.

61. (currently amended) An apparatus comprising:

authenticating logic operably coupled to authenticate a host device;

Serial No. 09/607007

- 16 -

Art Unit:2143

access logic operably coupled to generate access information for the host device, the access information including authentication information unique to the host device; and distribution logic operably coupled to distribute the access information both to the host device and to a separate designated device for enabling the host device to access a shared multicast distribution tree through the designated device.

62. (original) The apparatus of claim 61, wherein the access logic is operably coupled to generate an access token for the host device including the access information.

63. (original) The apparatus of claim 62, wherein the access token comprises:

a group identifier for identifying a multicast group;

a host identifier for identifying the host device;

a token identifier for identifying the access token;

an authentication key for the host device;

an expiration date for the authentication key;

a server identifier for identifying a key server; and a public key for a key server.

64. (original) The apparatus of claim 61, wherein the distribution logic comprises:

group key management logic operably coupled to send the access information to the host device.

65. (original) The apparatus of claim 61, wherein the distribution logic comprises:

unicasting logic operably coupled to send the access information to the designated device using a unicast mechanism.

66. (original) The apparatus of claim 61, wherein the distribution logic comprises:

multicasting logic operably coupled to send the access information to the designated device using a multicast mechanism.

67. (original) The apparatus of claim 61, wherein the distribution logic comprises:

Serial No. 09/607007

- 17 -

Art Unit:2143

broadcasting logic operably coupled to send the access information to the designated device using a broadcast mechanism.

68. (currently amended) A computer program for controlling a key server in a computer system, the computer program comprising:

 authenticating logic programmed to authenticate a host device;

 access logic programmed to generate access information for the host device the access information including authentication information unique of the host device; and

 distribution logic programmed to distribute the access information to the host device and to a separate designated device for enabling the host device to access a shared multicast distribution tree through the designated device.

69. (original) The computer program of claim 68, wherein the access logic is programmed to generate an access token for the host device including the access information.

70. (original) The computer program of claim 69, wherein the access token comprises:

a group identifier for identifying a multicast group;

 a host identifier for identifying the host device;

 a token identifier for identifying the access token;

 an authentication key for the host device;

 an expiration date for the authentication key;

 a server identifier for identifying a key server; and a public key for a key server.

71. (original) The computer program of claim 68, wherein the distribution logic comprises:

 group key management logic programmed to send the access information to the host device:

72. (original) The computer program of claim 68, wherein the distribution logic comprises:

 unicasting logic programmed to send the access information to the designated device using a unicast mechanism.

Serial No. 09/607007

- 18 -

Art Unit:2143

73. (original) The computer program of claim 68, wherein the distribution logic comprises:
multicasting logic programmed to send the access information to the designated device using a multicast mechanism.

74. (original) The computer program of claim 68, wherein the distribution logic comprises:
broadcasting logic programmed to send the access information to the designated device using a broadcast mechanism.

75. (currently amended) An apparatus comprising:
receiving logic operably coupled to receive, from an access information server, access information unique to a host device, for the access information enabling the host device to join ~~joining a multicast group from an access information server;~~ and
access logic operably coupled to generate an access control message for joining the multicast group using the access information and to send the access control message to a designated device separate from the access information server and coupling the host device to for ~~joining~~ the multicast group.

76. (original) The apparatus of claim 75, wherein the access information comprises:
a token identifier; and an authentication key.

77. (original) The apparatus of claim 76, wherein the access logic is operably coupled to include
the token identifier in the access control message.

78. (original) The apparatus of claim 75, wherein the access logic is operably coupled to generate
authentication information using the access information and send the authentication information
to the designated device.

Serial No. 09/607007

- 19 -

Art Unit:2143

79. (original) The apparatus of claim 78, wherein the access logic is operably coupled to generate the authentication information by generating a digital signature using the access information and a predetermined digital signature scheme.

80. (original) The apparatus of claim 79, wherein the predetermined digital signature scheme comprises a keyed hash function.

81. (original) The apparatus of claim 80, wherein the keyed hash function comprises IPsec AH with HMAC-MD5.

82. (original) The apparatus of claim 80, wherein the keyed hash function comprises EPsec AH with HMAC-SHA1.

83. (original) The apparatus of claim 76, wherein the access information further comprises a token identifier.

84. (original) The apparatus of claim 83, wherein the access logic is operably coupled to include the token identifier in the access control message.

85. (original) The apparatus of claim 84, wherein the access control message is an Internet Group Management Protocol (IGMP) join request message including the token identifier.

86. (original) The apparatus of claim 75, wherein the access logic is operably coupled to establish a security agreement with the designated device using the access information.

87. (currently amended) A computer program for controlling a computer system, the computer program comprising:

receiving logic programmed to receive access information for joining a multicast group from an access information server, the access information including authentication information unique to a host device; and

Serial No. 09/607007

- 20 -

Art Unit:2143

access logic programmed to generate an access control message for joining the multicast group using the access information and to send the access control message to a designated device separate from the access information server and coupling the host device to for joining the multicast group.

88. (original) The computer program of claim 87, wherein the access information comprises:
a token identifier; and an authentication key.

89. (original) The computer program of claim 88, wherein the access logic is programmed to include the token identifier in the access control message.

90. (original) The computer program of claim 87, wherein the access logic is programmed to generate authentication information using the access information and send the authentication information to the designated device.

91. (original) The computer program of claim 90, wherein the access logic is programmed to generate the authentication information by generating a digital signature using the access information and a predetermined digital signature scheme.

92. (original) The computer program of claim 91, wherein the predetermined digital signature scheme comprises a keyed hash function.

93. (original) The computer program of claim 92, wherein the keyed hash function comprises EPsec AH with HMAC-MD5.

94. (original) The computer program of claim 92, wherein the keyed hash function comprises IPsec AH with HMAC-SHA1.

95. (original) The computer program of claim 88, wherein the access information further comprises a token identifier.

Serial No. 09/607007

- 21 -

Art Unit:2143

96. (original) The computer program of claim 95, wherein the access logic is programmed to include the token identifier in the access control message.

97. (original) The computer program of claim 96, wherein the access control message is an Internet Group Management Protocol (IGMP) join request message including the token identifier.

98. (original) The computer program of claim 87, wherein the access logic is programmed to establish a security agreement with the designated device using the access information.

99. (currently amended) An apparatus comprising:

receiving logic operably coupled to receive an access control message from a host device, the access control message including authentication information unique to the host device;

access logic operably coupled to determine whether the host device is authorized to access a shared multicast distribution tree based upon access information for the host device stored at the apparatus, the stored access information including authentication information unique to the host device and being received from a separate key server; and

joining logic operably coupled to join the shared tree on behalf of the host device if the access logic determines that the host device is authorized to access the shared tree.

100. (original) The apparatus of claim 99, wherein the access logic is operably coupled to obtain the access information for the host device from an access information server.

101. (original) The apparatus of claim 100, wherein the access logic is operably coupled to obtain the access information for the host device from the access information server prior to receiving the access control message from the host device.

Serial No. 09/607007

- 22 -

Art Unit:2143

102. (original) The apparatus of claim 100, wherein the access logic is operably coupled to obtain the access information for the host device from the access information server after receiving the access control message from the host device.

103. (original) The apparatus of claim 99, further comprising an access information database.

104. (original) The apparatus of claim 103, wherein the access logic is operably coupled to search the access information database for the access information for the host device and determine that the host device is not authorized to access the shared tree upon failing to find the access information for the host device in the access information database.

105. (original) The apparatus of claim 103, wherein the access logic is operably coupled to search the access information database for the access information for the host device and forward the access control message to a neighboring device upon failing to find the access information for the host device in the access information database.

106. The apparatus of claim 99, wherein the access information comprises:
a token identifier; and an authentication key.

107. The apparatus of claim 106, wherein the access control message includes the token identifier.

108. The apparatus of claim 106, wherein the access information further comprises an expiration date for the authentication key.

109. (original) The apparatus of claim 108, wherein the access logic is operably coupled to determine whether the host device is authorized to access the shared tree based upon the expiration date for the authentication key.

Serial No. 09/607007

- 23 -

Art Unit:2143

110. (original) The apparatus of claim 109, wherein the access logic is operably coupled to determine that the host device is not authorized to access the shared tree upon determining that the authentication key has expired based upon the expiration date for the authentication key.

111. (original) The apparatus of claim 109, wherein the access logic is operably coupled to forward the access control message to a neighboring device upon determining that the authentication key has expired based upon the expiration date for the authentication key.

112. (original) The apparatus of claim 99, wherein the access logic is operably coupled to authenticate the host device using the access information and a predetermined authentication scheme.

113. (original) The apparatus of claim 112, wherein the access logic is operably coupled to receive authentication information from the host device and authenticate the host device based upon the access information and the authentication information received from the host device.

114. (original) The apparatus of claim 113, wherein the authentication information comprises a digital signature, and wherein the access logic is operably coupled to verify the digital signature using the access information and a predetermined digital signature scheme.

115. (original) The apparatus of claim 114, wherein the predetermined digital signature scheme comprises a keyed hash function.

116. (original) The apparatus of claim 115, wherein the keyed hash function comprises EPsec AH with HMAC-MD5.

117. (original) The apparatus of claim 115, wherein the keyed hash function comprises GPsec AH with HMAC-SHA1.

Serial No. 09/607007

- 24 -

Art Unit:2143

118. (original) The apparatus of claim 112, wherein the access logic is operably coupled to determine that the host device is not authorized to access the shared tree upon determining that the authentication failed.

119. (original) The apparatus of claim 118, wherein the access logic is operably coupled to forward the access control message to a neighboring device upon determining that the authentication failed.

120. (original) The apparatus of claim 112, wherein the access logic is operably coupled to determine that the host device is authorized to access the shared tree upon determining that the authentication succeeded.

121. (original) The apparatus of claim 99, wherein the access information is operably coupled to e(original) upon determining that the host device is authorized to access the shared tree.

122. (currently amended) A computer program for controlling a computer system, the computer program comprising:

receiving logic programmed to receive an access control message from a host device, the access control information including authentication information unique to the host device;

access logic programmed to determine whether the host device is authorized to access a shared multicast distribution tree based upon stored access information for the host device, the stored access information including authentication information unique to the host device and being received from a separate key server; and

joining logic programmed to join the shared tree on behalf of the host device if the access logic determines that the host device is authorized to access the shared tree.

123. (original) The computer program of claim 122, wherein the access logic is programmed to obtain the access information for the host device from an access information server.

Serial No. 09/607007

- 25 -

Art Unit:2143

124. (original) The computer program of claim 123, wherein the access logic is programmed to obtain the access information for the host device from the access information server prior to receiving the access control message from the host device.

125. (original) The computer program of claim 123, wherein the access logic is programmed to obtain the access information for the host device from the access information server after receiving the access control message from the host device.

126. (original) The computer program of claim 122, further comprising an access information database.

127. (original) The computer program of claim 126, wherein the access logic is programmed to search the access information database for the access information for the host device and determine that the host device is not authorized to access the shared tree upon failing to find the access information for the host device in the access information database.

128. (original) The computer program of claim 126, wherein the access logic is programmed to search the access information database for the access information for the host device and forward the access control message to a neighboring device upon failing to find the access information for the host device in the access information database.

129. (original) The computer program of claim 122, wherein the access information comprises:
a token identifier; and an authentication key.

130. (original) The computer program of claim 129, wherein the access control message includes the token identifier.

131. (original) The computer program of claim 129, wherein the access information further comprises an expiration date for the authentication key.

Serial No. 09/607007

- 26 -

Art Unit:2143

132. (original) The computer program of claim 131, wherein the access logic is programmed to determine whether the host device is authorized to access the shared tree based upon the expiration date for the authentication key.

133. (original) The computer program of claim 132, wherein the access logic is programmed to determine that the host device is not authorized to access the shared tree upon determining that the authentication key has expired based upon the expiration date for the authentication key.

134. (original) The computer program of claim 132, wherein the access logic is programmed to forward the access control message to a neighboring device upon determining that the authentication key has expired based upon the expiration date for the authentication key.

135. (original) The computer program of claim 122, wherein the access logic is programmed to authenticate the host device using the access information and a predetermined authentication scheme.

136. (original) The computer program of claim 135, wherein the access logic is programmed to receive authentication information from the host device and authenticate the host device based upon the access information and the authentication information received from the host device.

137. (original) The computer program of claim 136, wherein the authentication information comprises a digital signature, and wherein the access logic is programmed to verify the digital signature using the access information and a predetermined digital signature scheme.

138. (original) The computer program of claim 137, wherein the predetermined digital signature scheme comprises a keyed hash function.

139. (original) The computer program of claim 138, wherein the keyed hash function comprises IPsec AH with HMAC-MD5.

Serial No. 09/607007

- 27 -

Art Unit:2143

140. (original) The computer program of claim 138, wherein the keyed hash function comprises IPsec AH with HMAC-SHA1.

141. (original) The computer program of claim 135, wherein the access logic is programmed to determine that the host device is not authorized to access the shared tree upon determining that the authentication failed.

142. (original) The computer program of claim 141, wherein the access logic is programmed to forward the access control message to a neighboring device upon determining that the authentication failed.

143. (original) The computer program of claim 135, wherein the access logic is programmed to determine that the host device is authorized to access the shared tree upon determining that the authentication succeeded.

144. (original) The computer program of claim 122, wherein the access information is programmed to establish a security association with the host device using the access information upon determining that the host device is authorized to access the shared tree.

145. (currently amended) A communication message embodied in a data signal, the communication message comprising a group key for a multicast group and access information for a host device,
wherein the access information comprises an expiration date for the authentication key.

146. (original) The communication message of claim 145, wherein the access information comprises:

- a token identifier; and
- an authentication key.

147. (cancelled)

Serial No. 09/607007

- 28 -

Art Unit:2143

148. (original) The communication message of claim 145, wherein the access information comprises an access token.

149. (original) The communication message of claim 148, wherein the access token comprises:

- a group identifier for identifying a multicast group;
- a host identifier for identifying the host device;
- a token identifier for identifying the access token;
- an authentication key for the host device;
- an expiration date for the authentication key;
- a server identifier for identifying a key server; and a public key for the key server.

150. (cancelled)

151. (cancelled)

152. (cancelled)